



Indoor Floor Standing LCD Kiosk Displays

Model

AU32KS AU43KS

AU49KS AU55KS

AU65KS

These indoor displays combine a sleek design with high reliability and multiple options.

They can be optioned as System On Chip kiosks with either Windows or Android onboard.

They can also be non touch, IR Touch or PCAP Touch depending on your customer and project requirements.

Features

- Slim Black Bezel
- Ultra Slim Enclosure, 20 mm Thickness
- High Transparency Tempered Glass Face
- Aluminum Alloy Frame
- Commercial LCD Panel
- IR Touch Screen, Multi 20 Points Touch
- Commercial Android Motherboard
- Fanless and Low-power System

Indoor Floor Standing LCD Kiosk Displays



ITEM TYPE	AU32KS	AU43KS	AU49KS	AU55KS	AU65KS
PANEL TYPE					
Panel Size	32"	43"	49"	55"	65"
Panel Type	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD	a-Si TFT-LCD
Active Area	698.4x392.85mm	941.184x529.416mm	1073.78x604 mm	1209.6x 680.4 mm	1428.48x803.52 mm
Touch Screen	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch	10 points IR/ Capacitive touch
Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
Brightness	350 Nits	350 Nits	350 Nits	350 Nits	350 Nits
Contrast Ratio	1200:1	1200:1	1200:1	1200:1	1200:1
Viewing Angle	178/178	178/178	178/178	178/178	178/178
Aspect Ratio	16:9	16:9	16:9	16:9	16:9
LED Life Time	50,000 hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
MOTHERBOARD					
Operating System	Windows 10		Android 7.1		
CPU	I5		Quad Core 1.8GHz 64bits, RK3288		
Memory	4G		2G		
Storage	128G SSD		8G		
Network	Wifi, RJ45		Wifi, RJ45		
Languages	English		English		
I/O Ports	USB2.0*2/ USB3.0*2/ HDMI out*1/VGA out*1/ RJ45 Lan port*1/ Speaker out*1/ Mic in*1		USB 2.0 *2, , RJ45 *1, HDMI Out *1, earphone port*1 Standard MicroSD Card Slot *1 (Support Max 128G		
Speakers	5W x2		5W x2		
ENVIRONMENT					
Operating System	0°C ~ 50°C				
Storage System	-20°C ~ 60°C				
POWER					
Power Supply	96~220 V				
Rated Frequency	50/60Hz				