



12RU CLASSIC SERIES

SPECIFICATIONS

- **Static loading:** 90kg
- **Width:** 600mm
- **Depth:** 550mm, 600mm
- Supplied standard with toughened glass front door (mesh available)
- Powder coated, black coloured
- Generous top and bottom cable entry
- L shaped vertical uprights adjustable forward and back
- **Material:** SPCC quality cold rolled steel
- **Thickness:** Mounting profile 2.0mm, mounting angle 1.5mm, others -.2mm
- **Surface Finish:** Degrease, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting.
- Compatible with 19" International Standard
- Quick release side panels
- RU Markings



Front Lock



Swing Gate



RU Markings



PDU8



Fixed Shelf



2 x Fan System

2 YEARS WARRANTY

12RU WALL MOUNT CABINETS

Model	W X D X H (mm)	Capacity	Shelf (s)	Fan (s)	PDU	Swing Gate	M3	Weight (kg)
W12RU550	600 x 550 X 635	12RU	1	No 2 x Optional 2FS	Yes	Yes	0.25	34
W12RU550F	600 x 550 X 635	12RU	1	2	Yes	Yes	0.25	34
W12RU600	600 X 600 X 635	12RU	1	No 2 x Optional 2FS	Yes	Yes	0.27	36
W12RU600F	600 X 600 X 635	12RU	1	2	Yes	Yes	0.27	36

FEATURES

- Heavy duty frame work
- 1 Shelf included
- Power Distribution Unit included
- Reversible front toughened glass door
- Revolving front and side locks
- Vented front and sides for cooling
- Provision for optional fans
- Rear Swing Gate
- Pre-punched holes for cabling
- 19" adjustable rails (front and back)