



4RU CLASSIC SERIES

SPECIFICATIONS

- **Static loading:** 60kg
- **Width:** 600mm
- **Depth:** 300mm, 450mm
- Supplied standard with toughened glass front door
- Powder coated, black coloured
- Generous top and bottom cable entry
- L shaped vertical uprights adjustable forward and back
- **Material:** SPCC quality cold rolled steel
- **Thickness:** Mounting profile 2.0mm, mounting angle 1.5mm, others -.2mm
- **Surface Finish:** Degrease, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting.
- Compatible with 19" International Standard
- Quick release side panels
- RU Markings



Front Lock



RU Markings



1 x Fan System (Optional)



Fixed Shelf (Optional)



PDU8 (Optional)

2 YEARS WARRANTY

4RU WALL MOUNT CABINETS

Model	W X D X H (mm)	Capacity	Shelf (s)	Fan (s)	PDU	Swing Gate	M3	Weight (kg)
W4RU300	600 x 300 x 280	4RU	Not Available	No 1 x Optional 1FS	No Optional PDU8	No	0.06	12
W4RU450	600 x 450 x 280	4RU	No Optional S450	No 1 x Optional 1FS	No Optional PDU8	No	0.085	14.5

FEATURES

- Heavy duty frame work
- Reversible front toughened glass door
- Revolving front and side locks
- Vented front and sides for cooling
- Provision for optional fan
- Pre-punched holes for cabling
- 19" adjustable rails (front and back)
- Black colour with clear front door