



Totally Integrated,
Collaborative & Interactive
Touch Hub for the 360
experience.



4K Capacitive touch screen

4K resolution provides an ideal medium for presentations.



Two Cameras

Two high definition cameras with 720P HD grade allow more vivid video conferencing.



Easy Connectivity

Various inputs including USB (touch and memory), HDMI from the side and RS232.




Side Speaker bar

For better sound experience with 2 x 20W speakers.



Aluminum Bezel

Premium and stylish design.



Drive the 360 like you would your smartphone

By touching your home button, you can directly access the Android home page for complete ease of use.



Android

5.1 (Lollipop) OS Version
Quad Core 1.2GHz CPU
2G DRAM.



HDi Connect

Available to display any device in the room. Simple one button press for wireless presentations.




Easy Pen

Walk up + use whiteboarding.



OPS PC

Integrated Windows 10 available.



Day and Time display

Day and Time viewable from User Interface.



Compatible

Compatible with Android and Mac.

LED PANEL

Diagonal size	84"(213.50 cm)
Display Resolution (Max.)	3840 X 2160 (QWUXGA)
Brightness (average)	350 cd/m
Viewing Angle	H: 178° / V: 178° (CR>=10)
Contrast ratio	1400:1(Typ.)
Supported Colors	1.06 B colors (10bit(D))
Response Time	5 ms (GTG)
Display Frame Rate	120Hz
Installation	Landscape Orientation

CONNECTIVITY

Front	-
Side	USB A x 2, USB B x 1, HDMI x 1 "HDMI x 3, UHD DP x 1, PC
Rear	RGB, Audio-In/Out, USB3.0 x 1, USB2.0 x 1, USB B x 1 , Speaker Out (R/L), Line out, RS-232C (D-sub 9-pin), RJ45"

MECHANICAL

Dimensions Landscape	2143 X 1190 X 110 mm
Weight	114kg (251 lbs)
VESA mount	600 x 400 (mm), M8 Screw
Front Glass	Tempered Glass 4.0t (Anti-glare Type)
Cooling	Fanless

ENVIRONMENTAL

Operating Temperature	0 ~ 40 °C (32 ~104°F)
Storage Temperature	- 20 ~ 60 °C (-4 ~ 140 °F)
Operating Humidity	20% to 80% RH (no condensation)

ACCESORIES

PCAP Pen x 1, Remote controller, HDMI Cable 3m, USB Cable (A-B) 3m, Power Cable, User Manual (CD)

TOUCH

Detect area	1860.48(H) x 1046.52(V) mm / 73.24"(H) x 41.20"(V)
Detection method	Projected Capacitive Touch Sensor
Touch tool	Stylus Pen or Hands
Accuracy	±2mm
Response time	< 10ms
Available Touch Point	PCAP : 60 Points
Operating Systems	Window 7, 8, 10 / MAC 10.10 ~ 10.11 Android 5.1
PC connector	USB

ANDROID

System version	Android 5.1
CPU	1.2GHz. Quad Core. 64bit
GPU	Hexa Core
RAM	2GB(DDR3)
FLASH	8GB

ELECTRIC

Power Requirement	100 - 240V AC, 50/60 (Hz)
Power Consumption	Max. 430W
Power Consump. (Standby)	< 0.5W
Speaker Output	20W + 20W Stereo (8-ohms)

OSD

OSD Control	RS232C, IR Remote controller, Touch
OSD Language	English / Français / Deutsch / Spanish / Dutch / Russian / Korean / Japanese / Chinese
OSD Key Lock	Support
Regulatory approvals	CB, CE, FCC, NRTL, RoHS, PSE, RCM

OPTIONS

OPS PC(AOPS-7080), Wall-mount(AB-900)

Totally Integrated,
Collaborative & Interactive
Touch Hub for the **360**
experience.