

**Two-Way Loudspeaker System**

The iD-MH-15-8 is a two-way structure plastic cabinet system with waterproof and sunscreening housing, designed for long distance sound reinforcement.

**Features**

- Strong plastic cabinet, waterproof and sunscreening
- High power output
- Accurate 100° x 100° constant direction to reduce sound interference and ensures clear sound



**Applications**

- Suitable for long/middle sound reinforcement distance
- Suitable for public venues such as stadiums, etc.

**Specifications**

- Frequency Response: 80Hz-18kHz ±3dB
- Drivers: 1x8" (200mm) / 2" voice coil LF, 1x1" (25mm) / 1.4" voice coil HF
- Input Voltage: 100V
- Power: 37.5W/75W/150W/OFF/8Ω
- Sensitivity: 96 dB 1 watt/1 metre
- Maximum SPL: 117 dB continuous, 123 dB peak
- Impedance: 8 ohms nominal
- Dispersion (-6 dB): 100° x 100°
- Crossover: 2.5 kHz passive
- IP Rating: IP56 (Applicable Standards – EN 60529: 1991 + A1: 2000 + A2: 2013)
- Dimensions: (W)300mm x (H)302mm x (D)334mm
- Weight: 10kg

**Overall Dimensions**

