

MITSUMARU

Smart Digital Signage

43MDI45TST
55MDI45TST

INTERACTIVE TABLETOP TOUCH SCREENS

43" / 55"



TEMPERED
GLASS



Mitsumaru's touch screen tabletop panels are the perfect solution for those unique signage applications. Available in 43" & 55", these panels are the ideal fit for those needing wayfinding services. Retail, museums, commercial buildings and shopping centres could also utilise Mitsumaru's range of tabletop touch panels. With 10 point capacitive touch and a fully glassed front, these panels are robust enough for installation in most locales.

With Android OS and Wi-Fi network connectivity, installation of customised and native Apps is seamless. Whatever your touch screen requirements are, Mitsumaru has the range to meet those needs.

fusion signage

Content is King...!! Mitsumaru's Smart Digital Signage range is complemented by Fusion Signage, Australasia's premier Content Management System. Let the Mitsumaru / Fusion partnership deliver your turn key digital signage solution.



450nit Brightness



16/7 Rated Display



Android OS



3 Year Commercial Warranty

Visit Mitsumaru & Fusion at:
www.mitsumaru.com.au
www.fusionsignage.com.au

Panel

Size	43	55
Active Display Area (H x V mm)	940 x 529	1209 x 680
Brightness	450 nits	
Resolution	1920 x 1080	
Aspect Ratio	16 : 9	
Backlight Adjustment	N / A	
Viewing Angle	178° /178°	
Backlight Configuration	LED	
Operation Life Cycle-mtbf(hours)	50,000	

Mechanical

Dimensions (W x H x D)	1120 x 1250 x 610 mm	1310 x 1265 x 633 mm
Net Weight Enclosure	75 kg	90 kg
Material Finishing	Steel	
Colour	Black - Fine Grain Powder Coating	
Glass	Tempered Glass Back Painted Black C	
Touch	10 Points Capacitive	

Power

AC Input	110 - 220 VAC , 50 / 60 Hz	
Power Consumption	75 w	95 w

Environmental

Operating Environment	Indoor
Operating Temperature	0° C~40° C
Operating Humidity	10%~80%
Operating Altitude	≤ 2000m

Media

OS	Android 7.1
CPU	RK3288 1.8GHz
GPU	Mali-T764
RAM	2GB (DDR3)
ROM	8GB (eMMC)
HDMI	HDMI Output (x 1)
USB Data Input	USB 2.0 (x 1)
Analog Audio Output	3.5mm Headphone Jack (x1)
Ethernet	RJ-45 (x 1)
Wi-Fi	802.11/b/g/n